



Modello	HY150	HY500 /HY500H	HY1000/HY1000H	HY2000/HY2000H	Model
Codice	TKB#HY10CC22_ / TKB#HY10CC11	TKC#HY20CC22_ TKC#HY20HC22_ / TKC#HY20CF21_ TKC#HY20HF21A	TKC#HY30CC22_ TKC#HY30HC22_ / TKC#HY30CF21_ TKC#HY20HF21A	TKC#HY40CC22_ TKC#HY40HC22_ / TKC#HY40CF21_ TKC#HY40HF21A	Code
Volume refrigerato (lt)*	150	500	1000	2000	Refrigerated volume (lt)*
Temperatura d'impiego	25°C				Operating temperature
Alimentazione	230V 50Hz / 115V 60Hz				Supply
Potenza frigorifera (in raffreddamento)	245 W * / 250 W*	470 W* / 410 W*	660 W* / 670 W*	870 W* / 830 W*	Cooling capacity (cooling)
Potenza elettrica (raffreddamento)	150 W *	190 W* / 200 W*	240 W* / 260 W*	350 W* / 310 W*	Power consumption (cooling)
Refrigerante ecologico 	R290 / R134a	R290	R290	R290	 Ecological refrigerant
Temperatura ambiente	+10° / +38 °C				Ambient temperature
Temperatura acqua	16°C - 22°C				Water temperature
Dimensioni (mm)	215x 361x 315(h)	310 x 310 x 416 (h)	310 x 310x 458 (h)	310 x 310x 500 (h)	Dimensions (mm)
Peso (kg)	12,2	16,5	19,7	21,4	Weight (kg)

\* Reported value refers to the following condition: room temperature 30°C, water temperature 25°C

\*\* Reported value refers to the following condition: room temperature 30°C, water temperature 8°C, considering a well insulated tank

Alla data are approximate and they may change without notice by TECO  
I dati in tabella sono indicativi e possono essere cambiati a giudizio TECO